


## FEATURES

- 3 Programmable tone generators
- Programmable white noise generator
- Programmable attenuation
- Simultaneous sounds
- TTL compatible
- Up to 4MHz clock input \*



## DESCRIPTION

The SN76489AN digital complex sound generator is an I<sup>2</sup>L/Bipolar IC designed to provide low cost tone/noise generation capability in microprocessor systems. The SN76489AN is a data bus based I/O peripheral.

## RECOMMENDED OPERATING CONDITIONS

PARAMETER	MIN	TYP	MAX	UNITS
Supply Voltage, $V_{CC}$	4.5	5.0	5.5	V
High Level Output Voltage, $V_{OH}$ (pin 4)			5.5	V
Low Level Output Current, $I_{OL}$ (pin 4)			2	mA
Operating Free-Air Temperature, $T_A$	0		70	°C

- \* Part SN76489AN is identical to the SN76494N except that the maximum clock input frequency is 4MHz (500kHz for the SN76494N). A "divide-by-eight" stage is included in the input circuitry and 32 clock pulses are required to load the data, compared to 4 pulses for the SN76494N.

## OPERATION-

## 1. TONE GENERATORS

Each tone generator consists of a frequency synthesis section and an attenuation section. The frequency synthesis section requires 10 bits of information (F0-F9) to define half the period of the desired frequency (n). F0 is the most significant bit and F9 is the least significant bit. This information is loaded into a 10 stage tone counter, which is decremented at a N/16 rate where N is the input clock frequency. When the tone counter decrements to zero, a borrow signal is produced. This borrow signal toggles the frequency flip-flop and also reloads the tone counter. Thus, the period of the desired frequency is twice the value of the period register.

The frequency can be calculated by the following:

$$f = \frac{N}{32n}$$

where N = ref clock in Hz  
n = 10 bit binary number

The output of the frequency flip-flop feeds into a four stage attenuator. The attenuator values, along with their bit position in the data word, are shown in Table 1. Multiple attenuation control bits may be true simultaneously. Thus, the maximum attenuation is 28 db.

Table 1 ATTENUATION CONTROL

<u>AO</u>	<u>BIT POSITION</u>			<u>WEIGHT</u>
	<u>A1</u>	<u>A2</u>	<u>A3</u>	
0	0	0	1	2 db
0	0	1	0	4 db
0	1	0	0	8 db
1	0	0	0	16 db
1	1	1	1	OFF

## 2. NOISE GENERATOR

The Noise Generator consists of a noise source and an attenuator. The noise source is a shift register with an exclusive OR feedback network. The feedback network has provisions to protect the shift register from being locked in the zero state.

TABLE 2 NOISE FEEDBACK CONTROL

<u>FB</u>	<u>CONFIGURATION</u>
0	"Periodic" Noise
1	"White" Noise

Whenever the noise control register is changed, the shift register is cleared. The shift register will shift at one of four rates as determined by the two NF bits. The fixed shift rates are derived from the input clock.

TABLE 3 NOISE GENERATOR FREQUENCY CONTROL

<u>BITS</u>		
<u>NFO</u>	<u>NFI</u>	<u>SHIFT RATE</u>
0	0	N/512
0	1	N/1024
1	0	N/2048
1	1	Tone generator #3 output

The output of the noise source is connected to a programmable attenuator as shown in Figure 4 (see page 11).

### 3. OUTPUT BUFFER/AMPLIFIER

The output buffer is a conventional operational amplifier summing circuit. It sums the three tone generator outputs and the noise generator output. The output buffer will generate up to 10mA.

To prevent oscillations in the output buffer, the output (pin 7) should be decoupled. This is done by putting 10 ohms in series with 0.1 $\mu$ F from pin 7 to ground ( see figure 2).

### 4. CPU to SN76489AN INTERFACE

The microprocessor interfaces with the SN76489AN by means of the 8 data lines and 3 control lines ( $\overline{WE}$ ,  $\overline{CE}$  and READY). Each tone generator requires 10 bits of information to select the frequency and 4 bits of information to select the attenuation. A frequency update requires a double byte transfer, while an attenuator update requires a single byte transfer.

If no other control registers on the chip are accessed, a tone generator may be rapidly updated by initially sending both bytes of frequency and register data, followed by just the second byte of data for succeeding values. The register address is latched on the chip, so the data will continue going into the same register. This allows the 6 most significant bits to be quickly modified for frequency sweeps.


## 5. CONTROL REGISTERS

The SN76489AN has 8 internal registers which are used to control the 3 tone generators and the noise source. During all data transfers to the SN76489AN, the first byte contains a three bit field which determines the destination control register. The register address codes are shown in Table 4.

TABLE 4		REGISTER ADDRESS FIELD			DESTINATION CONTROL REGISTER
R0	R1	R2			
0	0	0			Tone 1 Frequency
0	0	1			Tone 1 Attenuation
0	1	0			Tone 2 Frequency
0	1	1			Tone 2 Attenuation
1	0	0			Tone 3 Frequency
1	0	1			Tone 3 Attenuation
1	1	0			Noise Control
1	1	1			Noise Attenuation

## 6. DATA FORMATS

The formats required to transfer data are shown below.



7. The microprocessor selects the SN76489AN by placing  $\overline{CE}$  into the true state (low voltage). Unless  $\overline{CE}$  is true, no data can occur. When  $\overline{CE}$  is true, the  $\overline{WE}$  signal strobes the contents of the data bus to the appropriate control register. The data bus contents must be valid at this time.

The SN76489AN requires approximately 32 clock cycles to load the data into the control register. The open collector READY output is used to synchronize the microprocessor to this transfer and is pulled to the false state (low voltage) immediately following the leading edge of  $\overline{CE}$ . It is released to go to the true state (external pullup) when the data transfer is completed.

The data transfer timing is shown below.

DATA TRANSFER TIMING




Figure 1.

TABLE 5

FUNCTION TABLE\*

Inputs		Output
$\overline{CE}$	$\overline{WE}$	READY
L	L	L
L	H	L
H	L	H
H	H	H

\* This table is valid when the device is:  
 (1) not being clocked, and  
 (2) is initialized by pulling  $\overline{WE}$  and  $\overline{CE}$  high.

# ADVANCED CIRCUITS

SN76489AN

## 8. PIN ASSIGNMENT

The table below defines the SN76489AN pin assignment and describes the function of each pin.

<u>SIGNATURE</u>	<u>PIN</u>	<u>I/O</u>	<u>DESCRIPTION</u>
$\overline{CE}$	6	IN	Chip Enable - when active (low) data may be transferred from CPU to the SN76489AN.
DO(MSB)	3	IN	D0 through D7 - Input data bus through which the control data is input.
D1	2	IN	
D2	1	IN	
D3	15	IN	
D4	13	IN	
D5	12	IN	
D6	11	IN	
D7	10	IN	
VCC	16	IN	Supply Voltage (5V nom)
GND	8	OUT	Ground Reference
CLOCK	14	IN	Input Clock
$\overline{WE}$	5	IN	Write Enable - when active (low), $\overline{WE}$ indicates that data is available from the CPU to the SN76489AN.
READY	4	OUT	When active (high), READY indicates that the data has been read. When READY is low, the microprocessor should enter a wait state until READY is high.
N.C.	9		No external connection should be made in this pin.
AOUT	7	OUT	Audio Drive Out


# ADVANCED CIRCUITS

SN76489AN

Electrical characteristics over recommended operating conditions (unless otherwise noted)

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNITS
$I_I$ Input Current	$V_{IN} = \text{GND to } V_{CC}$ $\overline{CE}$		-25	-175	$\mu\text{A}$
$V_{OL}$ Low Level Output Voltage	$D0-D7, \overline{WE}, \text{CLK}$		-10	-70	$\mu\text{A}$
	$I_{OUT} = 2\text{mA}$ READY		.25	.4	V
$I_{CC}$ Supply Current	Outputs Open		30	50	mA
$C_I$ Input Capacitance				15	pF
$I_{OH}$ High Level Output Current	READY			10	$\mu\text{A}$
$V_{IH}$ High Level Input Voltage	$D0-D7, \overline{WE}, \overline{CE}, \text{CLK}$	2			V
$V_{IL}$ Low Level Input Voltage	$D0-D7, \overline{WE}, \overline{CE}, \text{CLK}$			.8	V
2dB Attenuation		1	2	3	dB
4dB Attenuation		3	4	5	dB
8dB Attenuation		7	8	9	dB
16dB Attenuation		15	16	17	dB

## EXTERNAL AUDIO OUTPUT INTERFACE



\*\* These capacitance values are determined by the frequency response desired and the audio amplifier used.

Figure 2.




# ADVANCED CIRCUITS

SN76489AN

Switching Characteristics,  $V_{CC} = 5V$ ,  $T_A = 25^\circ C$

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNITS
* $\overline{CE}$ to READY	$C_L = 225pF$				
$t_{PLL}$ , 50% to 50%	$R_L = 2K$ to $V_{CC}$		90	150	nS
$f_{clock}$ , Input Clock Frequency	Clock Transition Time (10% to 90%) $10\mu S$	DC	3.579	4	MHz
Setup Time, $t_{su}$ (see Figure 1)	DATA W.R.T. $\overline{WE}$	0			nS
	$\overline{CE}$ W.R.T. $\overline{WE}$	0			nS
Hold Time, $t_h$ (see Figure 1)	DATA W.R.T. READY	0			nS


\*  $\overline{CE}$  Pulse: 0-3V,  $t_{rise} \leq 7nS$ ,  $t_{fall} \leq 7nS$



$t_{PLL}$  TEST CIRCUIT


Figure 3.

## BLOCK DIAGRAM



## BLOCK DIAGRAM DESCRIPTION

This device consists of three programmable tone generators, a programmable noise generator, a clock scaler, individual generator attenuators and an audio summer output buffer. The SN76489AN has a parallel 8 bit interface through which the microprocessor transfers the data which controls the audio output.




SN76489A / SN76494 SCHEMATIC

Figure 4.

## N package

This dual-in-line package consists of a circuit mounted on a 16-lead frame and encapsulated within an electrically nonconductive plastic compound. The compound will withstand soldering temperature with no deformation and circuit performance characteristics remain stable when operated in high-humidity conditions. The package is intended for insertion in mounting-hole rows on 0.300-inch centers. Once the leads are compressed and inserted, sufficient tension is provided to secure the package in the board during soldering. Leads require no additional cleaning or processing when used in soldered assembly.

16-PIN N PLASTIC DUAL-IN-LINE PACKAGE OUTLINE



- NOTES: a. Each pin center line is located within 0.010 of its true longitudinal position.  
b. All dimensions are in inches unless otherwise noted.

